

SMOKE DETECTOR - PHOTOELECTRIC



WIRED INTERCONNECT

FEATURES & BENEFITS

- Hardwired interconnection for up to 24 alarms
- 9V battery included
- Dual spectrum to reduce nuisance alarming
- Separate hush/test button
- Hinged detachable base - easy push button open
- 'No Battery', 'No Close' feature
- Loop terminal provided
- Mounting holes line up with standard plaster brackets
- Base recessed for mains cabling - no need for large ceiling cut-away
- LED indicators
- 'Low Battery' audible warning
- 7 year warranty
- Improved resilience to EMI interference
- Suitable for wall or ceiling mounting
- 1 or 10 year battery backup.

SPECIFICATIONS

Sound level output:

- 85dB@3m

Wireless frequency:

- 433.42 MHz

Temperature range:

- 0 - 40°C*

Humidity Range:

- 5% - 93%

Dimensions:

- 133mm Ø x 49mm (H)

Conforms to:

- AS3786:2023
- ISO 12239:2021

*High temperatures can impact battery life.



Code	Description	Packing	MOQ	Ctn
DET-SMK/AC/1	Type A Photoelectric Smoke Detector - 240V - 1 yr Alkaline Battery	1	1	50
DET-SMK/AC/10	Type A Photoelectric Smoke Detector - 240V - 10yr Lithium Battery	1	1	50